

SKID POWER - Technical Specifications



Description

SKID POWER has been designed for skid steers in construction applications. It shows excellent traction as well as enhanced self-cleaning features. The tire features an extra deep tread along with extra sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER is the ideal tire for loose surfaces.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Skid Steer

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

Dimensions International Standard

Ply Rating	8
Section Width (mm)	254
Overall Diameter (mm)	775
Static Loaded Radius (mm)	355
Rolling Circumference (mm)	2286
Rim Rec	8.25

Load capacity (Kg)

km/h / bar	4.10
10	1880
15	1485
25	1370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 02:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..