

## AT 108 - Tekniska specifikationer



### Description

AT 108 är ett terrängdäck som passar till fyrhjulingar. Mönstret ger utmärkt komfort och prestanda på både vägen och åkern.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Fyrhjuling

Version	STANDARD
Type	TL
Tyre Size	AT 25 X 8 - 12

## Dimensions International Standard

Ply Rating	4
Section Width (mm)	212
Overall Diameter (mm)	630
Rim Rec	6.5 AT
Rim Alt	6.0 AT
ECE	E4-75R-0004988

## Load capacity (Kg)

km/h / bar	0.35
100	132

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 03:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..