

EARTHMAX SR 22 AS - Tekniska specifikationer



Description

EARTHMAX SR 22 AS (E-2**/G-2*/L-2**) är ett stålradialdäck speciellt utformat för att användas på snö och is och säkerställer optimala prestanda under alla årstider.

Däcket har ett unikt däckmönster med djupa mönsterkanaler och har en sammansättning speciellt framtagen för vinterförhållanden som ger överlägsna bromsegenskaper på is och snö, och förhindrar att stenar fastnar i mönstret under hela året.

EARTHMAX SR 22 AS har en låg blocktäthet och ett brett avtryck som ger utmärkt dragförmåga och stabilitet med jämnt slitage och lång livslängd.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Väghyvlare • Hjullastare

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	185 B/170 A8 /201 A2

Dimensions US Standard

Usa code	94073405
Overall Width (inch)	24
Overall Diameter (inch)	63.5
Static Loaded Radius (inch)	27.9
Rolling Circumference (inch)	191.5
Rim Rec	19.50/2.5
Star Rating	**/**/**
TRA Code	E2/G2/L2
Tread Depth	42

Load capacity (lbs)

mph / psi	18	22	25	29	33	36	40	44	58	62	65	69	73	76	80	83	87	91	94
30	-	-	-	-	-	-	-	-	16500	17100	18200	18700	19800	20400	-	-	-	-	-
25	6950	7850	8800	9900	10700	11700	12300	13200	-	-	-	-	-	-	-	-	-	-	-
5	-	-	-	-	-	-	-	-	-	-	-	-	-	27600	28300	29100	30000	30900	32000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 07:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..