

EARTHMAX SR 33 PLUS - Ladda ned faktablad



Description

EARTHMAX SR 33 PLUS är ett radialdäck med multiblockmönster som har konstruerats och designats särskilt för att ge enastående flyt- och dragförmåga på mjuka, sandiga, leriga och hårt packade underlag. Den kraftfulla stålradialstommen med stålbalten ger utmärkt hållbarhet och motståndskraft mot revor och punkteringar. EARTHMAX SR 33 PLUS besitter imponerande självrensande egenskaper och erbjuder överlägsen stabilitet.

UM

International Standard

Construction



RADIAL

Machinery

Industri: Universalfordon

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
16.00 R 20	STANDARD	173/170 G	11.25	10.00W, 10.0	448	1310	582	3974	TL	E11-54R-0017916

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 05:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..