

FL 252 - Tekniska specifikationer



Description

FL 252 är ett däck för höskörd med rotorvändare/strängvändare. Det passar även för gaffeltruckar som används för logistiktillämpningar. Däcket är mycket pålitligt och det speciella slitbanemönstret ger maximal stabilitet vid lyft.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Roterande harv
Industri: Gaffeltruck

Version	STANDARD
Type	TT
Tyre Size	5.00 - 8

Dimensions US Standard

Usa code	94006816
Ply Rating	8
Section Width (inch)	5.4
Overall Diameter (inch)	18.9
Rim Rec	3.00 D
Rim Alt	3.25 I

Load capacity (lbs)

mph / psi	120
15 LOAD WHEEL	2725
15 STEER WHEEL	2095
5 OTHER VEHICLES	2725
15 OTHER VEHICLES	2095
STATIC SIDE LOADER	3165

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/17/2025 4:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..