

# FLOTATION TR 678 - Tekniska specifikationer



## Description

FLOTATION TR 678 är specialkonstruerat för släpvagnar och arbetsfordon i lantbruket för körning på både väg och åker. Däcket möjliggör körning av väldigt tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning. Det ger utmärkt dragförmåga och erbjuder enastående självrensande egenskaper.

## UM

International Standard

## Construction

 BIAS

## Machinery

Lantbruk: Arbetsfordon • Släpvagn

|           |               |
|-----------|---------------|
| Version   | STEEL BELTED  |
| Type      | TL            |
| Tyre Size | 710/40 - 22.5 |
| LI/SS     | 173 A8        |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 707             |
| Overall Diameter (mm)      | 1165            |
| Static Loaded Radius (mm)  | 545             |
| Rolling Circumference (mm) | 3624            |
| Rim Rec                    | AG 24.00        |
| ECE                        | E11-106R-006011 |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 6.0  |
| 40         | 6500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 04:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..