

GIANT TRAX - Tekniska specifikationer



Description

GIANT TRAX är ett däck som passar kompaktlastare som används på tuffa underlag, till exempel på anläggningar för avfallshantering och återvinning samt i gruvor. Det extra djupa slitbanemönstret med bredare och kraftigare block ger bästa möjliga dragkraft, stabilitet och skydd mot punkteringar. Den speciella gummiblandningen i slitbanan ger ett utomordentligt skydd mot skär- och skrapskador och ger däckets en utmärkt slitstyrka i alla typer av terräng.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Kompaktlastare

Version	STANDARD
Type	TL
Tyre Size	14 - 17.5
LI/SS	155 A2

Dimensions International Standard

Ply Rating	14
Section Width (mm)	350
Overall Diameter (mm)	915
Static Loaded Radius (mm)	421
Rolling Circumference (mm)	2714
Rim Rec	10.50
ECE	E11-106R-006019

Load capacity (Kg)

km/h / bar	5.50
10	3875
15	3060
25	2830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 23:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..