

HARVESTER SPECIAL - Tekniska specifikationer



Description

HARVESTER SPECIAL är särskilt konstruerat för skördemaskiner. De dubbla, vinklade däcklackarna ger utmärkt dragförmåga på åkern och bekväm körning på väg. Den speciella mönsterdesignen skapar en stor kontaktyta för överlägsen stabilitet. HARVESTER SPECIAL har ett starkt däckhölje och gummiblandningen ger extra motståndskraft mot skärande underlag och punkteringar för att garantera längre livslängd.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Skördemaskin

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26
LI/SS	155 A8

Dimensions US Standard

Usa code	94062089
Ply Rating	16
Section Width (inch)	23.1
Overall Diameter (inch)	62.4
Static Loaded Radius (inch)	28.3
Rolling Circumference (inch)	189.2
Rim Rec	DW 20 B ; DW 20 A
TRA Code	R1

Load capacity (lbs)

mph / psi	34
25	8550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 12:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..