

LG SMOOTH - Tekniska specifikationer



Description

LG SMOOTH är ett däck för gräsklippningsmaskiner som används på gräsmattor och i trädgårdar. Den förbättrade designen gör däckets skonsamt mot marken samtidigt som den ökar däckets pålitlighet och förenklar manövreringen. LG SMOOTH finns även tillgängligt i en aramidbältad version för användare som behöver däck med extra skydd mot punkteringar.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Åkgräsklippare • Liten traktor

Version	STANDARD
Type	TL
Tyre Size	20 X 10.00 - 10

Dimensions International Standard

Ply Rating	6
Section Width (mm)	245
Overall Diameter (mm)	500
Static Loaded Radius (mm)	223
Rolling Circumference (mm)	1450
Rim Rec	8.00 I - 55
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005202

Load capacity (Kg)

km/h / bar	2.20
15	660

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 7:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..