

PORT KING PLUS - Ladda ned faktablad



Description

PORT KING PLUS är särskilt avsett för reach stacker-truckar som används för intermodala transporter och logistiktillämpningar. Det djupa mönstret med kraftiga block ger, tillsammans med den speciella gummiblandningen, däckets längre livslängd. Det här däckets finns även tillgängligt med GCRC-gummiblandning (Groove Crack Resistant tread Compound).

UM

US Standard

Construction

 BIAS

Machinery

Industri: Reachstacker

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
18.00 - 25	GCRC	94026593	IND4	40	13.00 /2.5	15.00/2.5	20.8	65.9	30.1	195.1	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 05:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..