

RIB TRAILER - Tekniska specifikationer



Description

RIB TRAILER är ett diagonaldäck specialdesignat för körning på väg och offroad med arbetsfordon, framför allt halmskärare.

Konstruktionen med fyra mönsterringor optimerar lastfördelningen och det starka höljet ger motståndskraft mot stubb. RIB TRAILER har designats med en speciell gummiblandning som ger däckets extra lång livslängd tack vare den höga slitstyrkan.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS	94 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	170
Overall Diameter (mm)	735
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5 K ; 5.00 F

Load capacity (Kg)

km/h / bar	4.50
30	670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 7:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..