

## RIDEMAX IT 696 - Ladda ned faktablad



### Description

RIDEMAX IT 696 har en unik mönsterdesign och ett brett avtryck som ger utmärkt grepp vid körning på väg, även i vinterväglag. Däcket lämpar sig bäst för transporter och kommun/underhåll, tack vare egenskaper för höga hastigheter och det starka däckhöljet. Mönsterdesignen har tagits fram speciellt för tung tjänst och säkerställer ett lågt rullningsmotstånd som ger bättre bränsleekonomi och fantastisk stabilitet.

### UM

US Standard

### Construction



RADIAL

### Machinery

Lantbruk: Traktor

| SIZE                           | Version  | USACode  | LI/SS        | RIM REC            | RIM ALT                 | SW   | OD   | SLR  | RC    | Type | TMPH | ECE             |
|--------------------------------|----------|----------|--------------|--------------------|-------------------------|------|------|------|-------|------|------|-----------------|
| 240/70 R 16 IND                | STANDARD | 94067503 | 107A8/107B   | W8                 | W9                      | 9.6  | 29.2 | 13.5 | 87.6  | TL   | 0    | E11-106R-006942 |
| 340/80 R 18 IND                | STANDARD | 94048960 | 143 A8/138 D | 11 ; 11 SDC ; W 11 | W 10 ; 12 ; 12 SDC      | 13.5 | 39.4 | 18   | 117.3 | TL   | 0    | E11-106R-002987 |
| 360/80 R 20 IND                | STANDARD | 94071074 | 143D/147A8   | 11                 | W 10 ; W 11 ; 12 ; W 12 | 14.1 | 42.7 | 19.2 | 127.4 | TL   | 0    | E11-106R-007845 |
| 300/80 R 24 IND<br>(11.2 R 24) | STANDARD | 94033881 | 133 A8/128 D | DW 10              |                         | 11.6 | 42.9 | 19.7 | 129.8 | TL   | 0    | E4-106R-002292  |
| 340/80 R 24 IND<br>(12.4 R 24) | STANDARD | 94033843 | 140 A8/135 D | DW 11              | W 10 ; W 12 ; DW 10     | 13.5 | 45.4 | 20.5 | 135.6 | TL   | 0    | E4-106R-002293  |
| 360/80 R 24 IND<br>(13.6 R 24) | STANDARD | 94057252 | 143 A8/138 D | DW 11              | W 12 ; W 10             | 13.5 | 46.7 | 21.1 | 140   | TL   | 0    | E11-106R-004753 |
| 400/80 R 24 IND<br>(14.9 R 24) | STANDARD | 94038640 | 149 A8/144 D | DW 13              | W 12 ; W 14 L           | 15.9 | 49.2 | 22   | 148   | TL   | 0    | E4-106R-002400  |
| 420/65 R 24 IND                | STANDARD | 94058464 | 146 D/151 A8 | DW 13 L ; W13      | DW 15 L ; DW 14 L       | 16.5 | 45.6 | 20.9 | 137.1 | TL   | 1    | E11-106R-005952 |
| 440/80 R 24 IND<br>(16.9 R 24) | STANDARD | 94057269 | 154 A8/149 D | DW 14 L            | DW 15 L ; DW 13         | 17.4 | 51.7 | 23.2 | 155.1 | TL   | 0    | E11-106R-004760 |
| 460/65 R 24 IND                | STANDARD | 94058655 | 151 D/156 A8 | DW 14 L            | DW 15 L ; DW 13         | 17.9 | 47.8 | 21.6 | 143.5 | TL   | 1    | E11-106R-005109 |
| 500/70 R 24 IND                | STANDARD | 94067862 | 157 A8/152 D | DW 16 L            | DW 15 L ; DW 18 L       | 19.8 | 51.6 | 23.7 | 155.7 | TL   | 0    | E11-106R-007051 |
| 500/70 R 24 IND                | STANDARD | 94070244 | 164A8/159D   | DW 16 L            | DW 15 L ; DW 18 L       | 19.8 | 51.6 | 23.7 | 155.7 | TL   | 0    | E11-106R-007547 |
| 400/80 R 28 IND<br>(14.9 R 28) | STANDARD | 94039227 | 151 A8/146 D | W 13               | W 12 ; W 14 L           | 15.9 | 53.2 | 24.2 | 159.4 | TL   | 0    | E4-106R-002401  |
| 440/80 R 28 IND<br>(16.9 R 28) | STANDARD | 94034895 | 156 A8/151 D | W 14 L             | W 15 L                  | 17.4 | 55.7 | 25   | 168.8 | TL   | 0    | E4-106R-002299  |
| 440/80 R 30 IND<br>(16.9 R 30) | STANDARD | 94035816 | 157 A8/153 D | W 14 L             | W 15 L                  | 17.4 | 57.7 | 26.3 | 175.4 | TL   | 0    | E4-106R-002297  |
| 480/80 R 30 IND<br>(18.4 R 30) | STANDARD | 94033850 | 162 A8/157 D | W 15 L             | W 16 L                  | 18.9 | 60.2 | 27   | 180.2 | TL   | 0    | E4-106R-002298  |
| 440/80 R 34 IND<br>(16.9 R 34) | STANDARD | 94038657 | 159 A8/155 D | DW 14 L            | DW 15 L ; DW 16 L       | 17.4 | 61.7 | 27.7 | 188   | TL   | 0    | E4-106R-002295  |
| 480/80 R 34 IND<br>(18.4 R 34) | STANDARD | 94035106 | 164 A8/159 D | W 15 L             | W 16 L                  | 18.9 | 64.3 | 28.7 | 192.7 | TL   | 0    | E4-106R-002296  |
| 480/80 R 38 IND<br>(18.4 R 38) | STANDARD | 94033867 | 166 A8/161 D | W 15 L             | W 16 L                  | 18.9 | 68.2 | 30.7 | 205.2 | TL   | 0    | E11-106R-004075 |
| 540/80 R 38 IND                | STANDARD | 94055838 | 172 A8/167 D | W 18 L             | W 16 L                  | 21.7 | 72   | 32.8 | 218   | TL   | 0    | E11-106R-004077 |
| 540/80 R 42 IND                | STANDARD | 94062409 | 168 D/173 A8 | W 18 L             | W 16 L                  | 22   | 76   | 34.6 | 231.3 | TL   | 0    | E11-106R-005714 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..