

ROCK STAR IND4 - Tekniska specifikationer



Description

ROCK START PORT IND-4 har utformats särskilt för tomma containerhanterare och gaffeltruckar. Förutom utmärkt dragkraft ger den unika slitbanan överlägset motstånd mot skär- och skrapskador. ROCK START PORT IND-4 säkerställer enastående lastkapacitet och överlägsen hållbarhet.

UM

International Standard

Construction

✚ BIAS

Machinery

Industri: Tomcontainerhanterare • Gaffeltruck

Version	PORT INDUSTRIAL
Type	TT
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	390
Overall Diameter (mm)	1425
Static Loaded Radius (mm)	635
Rolling Circumference (mm)	4350
Rim Rec	10.00 W
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	13500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 01:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..