

SKID POWER HD (B) - Tekniska specifikationer



Description

SKID POWER HD (B) är avsett för användning på kompaktlastare i bygg- och anläggningsbranschen. Det extra djupa mönstret och skyddet för sidoväggen ger det här däck ett utomordentligt skydd mot skär- och skrapskador samt enastående pålitlighet. SKID POWER HD (B) är idealiskt att använda på lösa underlag och vid tunga arbeten.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Kompaktlastare

Version	STANDARD
Type	TL
Tyre Size	18 X 8.5 - 10
LI/SS	96 A2

Dimensions International Standard

Ply Rating	8
Section Width (mm)	205
Overall Diameter (mm)	465
Static Loaded Radius (mm)	211
Rolling Circumference (mm)	1393
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-006774

Load capacity (Kg)

km/h / bar	3.00
10	720
15	570
25	525

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18.05.2025 04:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..