

## SM 55 L5S - Tekniska specifikationer



### Description

SM 55 (L-5S) är ett diagonaldäck för användning i gruvdrift under jord. Den specialdesignade skär- och rivtåliga gummixblandningen i slitbanan minimerar antalet punkteringar och efterföljande stilleståndstid. Det extra djupa L-5S-mönstret garanterar en längre livscykel. Däcket finns även tillgängligt i en version med stålbelten.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Dumper med lågprofil • Underjordiskt gruvfordon

|           |              |
|-----------|--------------|
| Version   | STEEL BELTED |
| Type      | TL           |
| Tyre Size | 26.5 - 25    |

## Dimensions International Standard

|                            |           |
|----------------------------|-----------|
| Ply Rating                 | 32        |
| Overall Width (mm)         | 700       |
| Overall Diameter (mm)      | 1798      |
| Static Loaded Radius (mm)  | 816       |
| Rolling Circumference (mm) | 5322      |
| Rim Rec                    | 22.00/3.0 |
| TRA Code                   | L5S       |
| Tread Depth                | 96        |

## Load capacity (Kg)

|            |       |
|------------|-------|
| km/h / bar | 5.50  |
| 10         | 17000 |
| 15         | 14790 |
| 25         | 13600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 5:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..