

SM 55 L5S - Tekniska specifikationer



Description

SM 55 (L-5S) är ett diagonaldäck för användning i gruvdrift under jord. Den specialdesignade skär- och rivtåliga gummixblandningen i slitbanan minimerar antalet punkteringar och efterföljande stilleståndstid. Det extra djupa L-5S-mönstret garanterar en längre livscykel. Däcket finns även tillgängligt i en version med stålbelten.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Dumper med lågprofil • Underjordiskt gruvfordon

Version	STEEL BELTED
Type	TL
Tyre Size	29.5 - 29

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	755
Overall Diameter (mm)	2020
Static Loaded Radius (mm)	882
Rolling Circumference (mm)	6021
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5
TRA Code	L5S
Tread Depth	104

Load capacity (Kg)

km/h / bar	4.25
10	19000
15	16530
25	15200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 5:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..