

## SR 713 - Tekniska specifikationer



### Description

SR 713 är ett radialdäck helt i stål med VF-teknologi för jordbrukstillämpningar. Däcket har ett flerskiktigt stålbalteshölje och flera mönsterribbor som säkerställer lågt rullmotstånd och jämnt mönsterslitage. Tack vare sitt stora avtryck ger det här VF-däcket minskad jordpackning. SR 713 är överlägset i både prestanda och pålitlighet samt erbjuder enastående hastigheter på vägen.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Arbetsfordon

|           |                  |
|-----------|------------------|
| Version   | STANDARD         |
| Type      | TL               |
| Tyre Size | VF 295/75 R 22.5 |
| LI/SS     | 155 D            |

# Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Overall Width (mm)         | 280             |
| Overall Diameter (mm)      | 1020            |
| Static Loaded Radius (mm)  | 449             |
| Rolling Circumference (mm) | 3044            |
| Rim Rec                    | 9.00            |
| Rim Alt                    | 8.25            |
| ECE                        | E11-106R-006977 |
| TRA Code                   | I1              |

## Load capacity (Kg)

| km/h / bar | 2.4  | 2.6  | 2.8  | 3    | 3.2  | 3.4  | 3.6  | 3.8  | 4    | 4.2  | 4.4  | 4.6  | 4.8  |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 0          | 4875 | 5150 | 5590 | 5920 | 6095 | 6265 | 6670 | 6900 | 7245 | 7705 | 7935 | 8395 | 8915 |
| 10         | 3815 | 4030 | 4375 | 4635 | 4770 | 4905 | 5220 | 5400 | 5670 | 6030 | 6210 | 6570 | 6975 |
| 15         | 3670 | 3875 | 4205 | 4455 | 4585 | 4715 | 5015 | 5190 | 5450 | 5795 | 5970 | 6315 | 6705 |
| 25         | 3350 | 3540 | 3840 | 4070 | 4185 | 4305 | 4580 | 4740 | 4975 | 5295 | 5450 | 5765 | 6125 |
| 30         | 3200 | 3380 | 3670 | 3890 | 4000 | 4115 | 4380 | 4530 | 4755 | 5060 | 5210 | 5510 | 5850 |
| 40         | 2885 | 3045 | 3305 | 3500 | 3605 | 3705 | 3945 | 4080 | 4285 | 4555 | 4690 | 4965 | 5270 |
| 50         | 2565 | 2710 | 2940 | 3115 | 3205 | 3295 | 3510 | 3630 | 3810 | 4055 | 4175 | 4415 | 4690 |
| 60         | 2270 | 2395 | 2600 | 2755 | 2835 | 2915 | 3105 | 3210 | 3370 | 3585 | 3690 | 3905 | 4145 |
| 65         | 2120 | 2240 | 2430 | 2575 | 2650 | 2725 | 2900 | 3000 | 3150 | 3350 | 3450 | 3650 | 3875 |
| 70         | 1930 | 2040 | 2210 | 2345 | 2410 | 2480 | 2640 | 2730 | 2865 | 3050 | 3140 | 3320 | 3525 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 10:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..