

SR 713 - Tekniska specifikationer



Description

SR 713 är ett radialdäck helt i stål med VF-teknologi för jordbrukstillämpningar. Däcket har ett flerskiktigt stålbalteshölje och flera mönsterribbor som säkerställer lågt rullmotstånd och jämnt mönsterslitage. Tack vare sitt stora avtryck ger det här VF-däcket minskad jordpackning. SR 713 är överlägset i både prestanda och pålitlighet samt erbjuder enastående hastigheter på vägen.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Arbetsfordon

Version	STANDARD
Type	TL
Tyre Size	VF 445/65 R 22.5
LI/SS	169 D

Dimensions International Standard

Overall Width (mm)	440
Overall Diameter (mm)	1160
Static Loaded Radius (mm)	533
Rolling Circumference (mm)	3515
Rim Rec	13.00
Rim Alt	14.00
ECE	E11-106R-005501
TRA Code	I1

Load capacity (Kg)

km/h / bar	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
65	3550	3750	4000	4250	4375	4625	4750	5000	5300	5450	5800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 6:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..