

## TR 135 - Tekniska specifikationer



### Description

TR 135 lämpar sig bäst för traktorer som används till jordbearbetning. Det förstärkta däckhöljet och gummblandningens speciella motståndskraft mot skärande underlag och punkteringar ger extra lång livslängd. Dragförmåga, självrensande egenskaper och lastkapacitet är avgörande egenskaper som gör TR 135-däcket till det idealiska valet även vid de mest krävande markförhållanden.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Traktor  
Industri: Släpvagn

|           |                        |
|-----------|------------------------|
| Version   | STANDARD               |
| Type      | TT                     |
| Tyre Size | 15 - 30<br>(18.4 - 30) |
| LI/SS     | 151 A6                 |

## Dimensions International Standard

|                            |        |
|----------------------------|--------|
| Ply Rating                 | 14     |
| Section Width (mm)         | 460    |
| Overall Diameter (mm)      | 1545   |
| Static Loaded Radius (mm)  | 714    |
| Rolling Circumference (mm) | 4542   |
| SRI (mm)                   | 725    |
| Rim Rec                    | W 16 L |
| Rim Alt                    | W 15 L |
| TRA Code                   | R1     |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 2.60 |
| 30         | 3450 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 09:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..