

TR 135 - Tekniska specifikationer



Description

TR 135 lämpar sig bäst för traktorer som används till jordbearbetning. Det förstärkta däckhöljet och gummblandningens speciella motståndskraft mot skärande underlag och punkteringar ger extra lång livslängd. Dragförmåga, självrensande egenskaper och lastkapacitet är avgörande egenskaper som gör TR 135-däcket till det idealiska valet även vid de mest krävande markförhållanden.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Traktor
Industri: Släpvagn

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26
LI/SS	159 A6

Dimensions International Standard

Ply Rating	16
Section Width (mm)	587
Overall Diameter (mm)	1585
Static Loaded Radius (mm)	700
Rolling Circumference (mm)	4615
SRI (mm)	750
Rim Rec	DW 20 B ; DW 20 A
ECE	E11-106R-004598
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.30
30	4375

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 05:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..