

TR 393 (B) - Tekniska specifikationer



Description

TR 393 (B) är specialkonstruerat för såmaskiner, spridare och arbetsfordon för körning på både väg och åker. Det speciella däckmönstret ger optimal flotation och självrensande egenskaper, samt lång livslängd. Tack vare den stora kontaktytan ger TR 393 (B) utmärkt dragförmåga och minimerar jordpackning.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Arbetsfordon • Spridare

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	31 X 13.50 - 15
LI/SS	124 B

Dimensions US Standard

Usa code	94070626
Ply Rating	12
Section Width (inch)	13.8
Overall Diameter (inch)	30.6
Rim Rec	10 LB
ECE	E11-106R-008131
TRA Code	R3

Load capacity (lbs)

mph / psi	75
30	3520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/17/2025 4:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..