

TR 461 - Tekniska specifikationer



Description

TR 461 har ett BKT-mönster som passar traktorer för kommunala arbeten och underhållsarbeten samt lastningsarbeten med teleskoplastare. Skyddet för sidoväggen ger det här däck utmärkt stabilitet och ett utomordentligt skydd mot skär- och skrapskador, vilket ger längre livslängd även på hårda ytor.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Grävlastare • Teleskoplastare • Traktor

Version	STANDARD
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	138 A8
LI/SS FREE ROLLING	150 A8

Dimensions US Standard

Usa code	94067428
Ply Rating	18
Section Width (inch)	12
Overall Diameter (inch)	38.9
Static Loaded Radius (inch)	17.1
Rolling Circumference (inch)	114.3
Rim Rec	W 9
Rim Alt	11
ECE	E11-106R-006914
TRA Code	R4

Load capacity (lbs)

mph / psi	80
5 FR	10340
15 FR	8780
20 FR	8270
25 FR	7390
5 DW	7290
15 DW	6190
20 DW	5830
25 DW	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 23:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..