

TF 9090 - Technical Specifications



Description

TF 9090 is a tire designed for small tractors in soil tillage operations. The special tread design provides excellent steering performance on loose soil.

UM

US Standard

Construction



Machinery

Agriculture: Small Tractor

Industrial: Trailer

Version	STANDARD
Туре	π
Tyre Size	10.00 - 16
LI/SS	111 A8

Dimensions US Standard

Usa code	94032501
Ply Rating	10
Section Width (inch)	10.8
Overall Diameter (inch)	35.4
Static Loaded Radius (inch)	16.1
Rolling Circumference (inch)	106.9
Rim Rec	W 8
Rim Alt	W 8 L
ECE	E4-106R-002671
TRA Code	F2

Load capacity (lbs)

mph / psi	86
25	2400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 23:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..