

TR 126 - Data Sheet



Description

TR 126 is designed to fit small tractors in soil tillage operations. The deep lugs and the tread pattern provide excellent traction and outstanding load capacity features providing best tire performance in all operating conditions.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Small Tractor

| SIZE | Version | USACode | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|--------|----------|----------|----------|-------|----|-------------|---------|-----|------|------|------|------|-----------------|
| 6 - 14 | HD | 94069972 | R1 | 77 A8 | 8 | 5 JA ; 5 KB | | 6.2 | 25.8 | 12 | 77.9 | TT | E11-106R-007418 |
| 6 - 14 | STANDARD | 94053513 | R1 | 63 A8 | 4 | 5 JA ; 5 KB | | 6.2 | 25.8 | 12 | 77.9 | TL | E11-106R-003476 |
| 6 - 14 | STANDARD | 94004522 | R1 | 63 A8 | 4 | 5 JA ; 5 KB | | 6.2 | 25.8 | 12 | 77.9 | TT | E11-106R-003476 |
| 7 - 14 | STANDARD | 94052639 | R1 | 92 A8 | 8 | 5 JA ; 5 KB | | 6.7 | 27.2 | 12.6 | 81.5 | TT | E11-106R-005233 |
| 7 - 14 | STANDARD | 94053520 | R1 | 68 A8 | 4 | 5 JA ; 5 KB | | 6.7 | 27.2 | 12.6 | 81.5 | TL | E11-106R-003356 |
| 7 - 14 | STANDARD | 94004539 | R1 | 68 A8 | 4 | 5 JA ; 5 KB | | 6.7 | 27.2 | 12.6 | 81.5 | TT | E11-106R-003356 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 17:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..