

## TR 133 - Technical Specifications



### Description

TR 133 has been specially designed for tractors in soil tillage applications. Thanks to the increased number of lugs, this tire features excellent traction as well as enhanced self-cleaning properties. TR 133 provides an extended tire life-cycle.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TT
Tyre Size	13.6 - 38 (14.00 - 38)
LI/SS	136 A6

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	350
Overall Diameter (mm)	1580
Static Loaded Radius (mm)	735
Rolling Circumference (mm)	4843
SRI (mm)	750
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-003549
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.50
30	2240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 01:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..