

TR 136 - Technical Specifications



Description

TR 136 has been developed by BKT to equip tractors and trailers in soil tillage and haulage operations. This tire provides improved traction in all working conditions along with best cut and chip resistance to reduce machine downtime and increase your productivity. Thanks to the increased number of lugs, TR 136 provides outstanding traction even at high loads.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Tractor • Trailer

Version	HD
Type	TT
Tyre Size	18.4 - 30
LI/SS	147 A8

Dimensions US Standard

Usa code	94004133
Ply Rating	14
Section Width (inch)	18.4
Overall Diameter (inch)	61
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	185.8
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-003615
TRA Code	R1

Load capacity (lbs)

mph / psi	38
25	6780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 21:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..