

## TR 317 - Data Sheet

### Description

TR 317 is suitable for municipality and soil tillage operations with implement machinery, trenchers and orchard harvesters. The TR 317 tire has a large contact area which provides excellent grip and outstanding stability in any condition along with great self-cleaning properties.

### UM

US Standard

### Construction

✚ BIAS

### Machinery

Agriculture: Implement Machinery • Orchard Harvester •  
Trencher



SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.50 - 8	HD	94045884	6	7.00 I - 55 ; I - 70 ; I - 90		8.5	17.7	7.8	51.4	TL	
18 X 8.50 - 8	STANDARD	94038879	4	7.00 I - 55 ; I - 70 ; I - 90		8.5	17.7	7.8	51.4	TL	E11-106R-003495

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 19:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..