

## AGRIMAX ELOS - Veri Sayfasını İndir



### Description

AGRIMAX ELOS çeltik tarlaları ve bataklıklar gibi ıslak arazilerde karşılaşılan, en zorlu çalışma koşullarında bile üstün çekiş performansını artırmak üzere tasarlanmıştır. Sırt dişlerinin tasarımı, taşıma işlemleri sırasında ve çamurlu arazilerdeki faaliyetlerde elzem olan, en yüksek kendini temizleme niteliklerini sağlamak için özel olarak geliştirilmiştir. Makinelerin çalışmama sürelerini azaltarak çiftçilerin verimliliğini en üst düzeye çıkarmak için, AGRIMAX ELOS'a yanak koruyucuları entegre edilerek her durumdaki olası zararlara karşı maksimum koruma sağlanmıştır.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: Traktör

| SIZE                                     | Version  | TRA Code | LI/SS        | RIM REC | RIM ALT                                                         | SW  | OD   | SLR | RC   | SRI | Type | ECE              |
|------------------------------------------|----------|----------|--------------|---------|-----------------------------------------------------------------|-----|------|-----|------|-----|------|------------------|
| <b>420/85 R 28</b><br><b>(16.9 R 28)</b> | STANDARD | R2       | 139 A8/B     | W 15 L  | W 13 ; W 14 L                                                   | 438 | 1467 | 665 | 4349 | 700 | TL   | E4-106R-000768   |
| <b>480/70 R 34</b>                       | STANDARD | R2       | 155 A8/155 B | W 15 L  | W 16 L ; W 14 L                                                 | 500 | 1605 | 733 | 4868 | 750 | TL   | E11-106R-007532  |
| <b>340/85 R 38</b><br><b>(13.6 R 38)</b> | STANDARD | R2       | 133 A8/B     | W 12    | W 11                                                            | 353 | 1602 | 735 | 4774 | 775 | TL   | E4-106R-001477   |
| <b>380/85 R 38</b><br><b>(14.9 R 38)</b> | STANDARD | R2       | 139 A8/B     | W 12    | W 11 ; W 13                                                     | 380 | 1662 | 772 | 4994 | 775 | TL   | E4-106R-000779   |
| <b>420/85 R 38</b><br><b>(16.9 R 38)</b> | STANDARD | R2       | 144 A8/B     | W 15 L  | W 13 ; W 14 L                                                   | 438 | 1735 | 785 | 5135 | 825 | TL   | E4-106R-000780   |
| <b>480/80 R 38</b><br><b>(18.4 R 38)</b> | STANDARD | R2       | 149 A8/B     | W 16 L  | W 15 L ; DW 16 L                                                | 489 | 1803 | 821 | 5356 | 825 | TL   | E11-106R-002991  |
| <b>710/70 R 38</b>                       | STANDARD | R2       | 178 A8/B     | DW 23 B | DW 25 B                                                         | 716 | 2019 | 915 | 6103 | 925 | TL   | E11-106R-004896  |
| <b>480/80 R 42</b><br><b>(18.4 R 42)</b> | STANDARD | R2       | 151 A8/B     | DW 16 L | DD 16 L ; W 16 L                                                | 489 | 1890 | 857 | 5629 | 875 | TL   | E4-106R-001481   |
| <b>520/85 R 42</b><br><b>(20.8 R 42)</b> | STANDARD | R2       | 157 A8/B     | DW 16 L | DD 18 L ; DW 18 L                                               | 516 | 1988 | 904 | 5865 | 925 | TL   | E4-106R-000793   |
| <b>520/85 R 42</b><br><b>(20.8 R 42)</b> | STANDARD | R2       | 167A8/B      | DW 16 L | DD 18 L ; DW 18 L                                               | 516 | 1988 | 920 | 6095 | 925 | TL   | E11-106R-0010146 |
| <b>520/85 R 46</b>                       | STANDARD | R2       | 169 A8/169 B | DW 16 L | DW 15 L ; DW 18 L ; W 15 L ; W 16 L ; W18 L ; DD 16 L ; DD 18 L | 530 | 2075 | 957 | 6293 | 975 | TL   | E11-106R-007935  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16/05/2025 17:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..