

AGRIMAX RT 765 - Teknik Özellikler



Description

BKT 70 serisi bir lastik olan AGRIMAX RT 765, toprak işleme, arazi ve kara yolu taşımacılığı, üzüm hasadı ve ilaçlama gibi çeşitli ağır hizmet uygulamalarına yönelik son teknoloji traktörler için uygundur. Geniş temas katmanı, tüm yüzeylerde her zaman mümkün olan en iyi çekiş ve konforu sağlar. Bu lastik mükemmel kendi kendini temizleme özellikleri ve daha az toprak sıkışması sağlar. Çelik kuşaklı teknolojiye sahip iki ebat mevcuttur.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama • Traktör • Üzüm hasat makinesi

Version	STANDARD
Type	TL
Tyre Size	620/70 R 42
LI/SS	166 D

Dimensions US Standard

Usa code	94063505
Section Width (inch)	24.6
Overall Diameter (inch)	76.2
Static Loaded Radius (inch)	34.5
Rolling Circumference (inch)	228.4
Rim Rec	DW 20 B
Rim Alt	DW 18 L
ECE	E11-106R-005998
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	5500	6320	7250	8180	9120	10050	10990	11680
30	5780	6640	7620	8600	9580	10560	11540	12270
25	6020	6910	7940	8960	9990	11010	12040	12800
20	6320	7260	8330	9410	10480	11560	12630	13440
5 LT	7360	8470	9720	10970	12220	13480	14730.	15660
5 HT	6320	7260	8330	9410	10480	11560	12630	13440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18/05/2025 2:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..