

AGRIMAX V-FLECTO - Teknik Özellikler



Description

AGRIMAX V-FLECTO, BKT'nin yüksek güçlü traktörlerde zorlu teknoloji ve performans talebine verdiği yanıttır. Bu lastik, daha az toprak sıkışması ve kendi kendini temizleme özellikleri sayesinde toprak işleme ve taşıma uygulamaları için mükemmeldir. Yenilikçi VF teknolojisi ile AGRIMAX V-FLECTO, standart ve IF lastiklere kıyasla daha düşük bir şişirme basıncıyla ağır yükleri taşıyıp yüksek hızlara ulaşabilir. Ayrıca, lastik üzerine standart jantların monte edilmesini sağlayan Dar Jant Seçeneğine sahiptir. BKT, bu lastiği hem tarlada hem de yolda sürüş konforunu artırmak için, yakıt tüketimini azaltan, optimize edilmiş geometri ile tasarladı.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Yüksek güçte traktör

Version	STANDARD
Type	TL
Tyre Size	VF 340/85 R 28
LI/SS	139 D

Dimensions US Standard

Usa code	94076369
Section Width (inch)	14
Overall Diameter (inch)	50.8
Static Loaded Radius (inch)	22.5
Rolling Circumference (inch)	150.9
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-0010342

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
45	2680	3110	3550	3990	4430	4870
from 40 to 25	2940	3430	3900	4390	4870	5360
20	3000	3480	3980	4460	4960	5460
12	3050	3560	4060	4560	5060	5570
5	3530	4710	5890	7050	8210	9370
*Upto 5 Cyc with front loader	4120	4790	5470	6140	6810	7500
10HT	3000	3480	3980	4460	4960	5460

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 09:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..