

AGRIMAX V-FLECTO - Teknik Özellikler



Description

AGRIMAX V-FLECTO, BKT'nin yüksek güçlü traktörlerde zorlu teknoloji ve performans talebine verdiği yanıttır. Bu lastik, daha az toprak sıkışması ve kendi kendini temizleme özellikleri sayesinde toprak işleme ve taşıma uygulamaları için mükemmeldir. Yenilikçi VF teknolojisi ile AGRIMAX V-FLECTO, standart ve IF lastiklere kıyasla daha düşük bir şişirme basıncıyla ağır yükleri taşıyıp yüksek hızlara ulaşabilir. Ayrıca, lastik üzerine standart jantların monte edilmesini sağlayan Dar Jant Seçeneğine sahiptir. BKT, bu lastiği hem tarlada hem de yolda sürüş konforunu artırmak için, yakıt tüketimini azaltan, optimize edilmiş geometri ile tasarladı.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Yüksek güçte traktör

Version	STANDARD
Type	TL
Tyre Size	VF 650/60 R 38 NRO
LI/SS	173 D

Dimensions US Standard

Usa code	94065370
Section Width (inch)	25.6
Overall Diameter (inch)	68.7
Static Loaded Radius (inch)	30.5
Rolling Circumference (inch)	205.4
Rim Rec	DW 23 B
Rim Alt	DW 21 B
Narrow Rim option	DW 20 B
ECE	E11-106R-006415
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	6010	6910	7960	8870	9920	10820	12140	13040
From 40 to 25	6590	7590	8740	9740	10890	11890	13330	14330
20	6720	7750	8920	9940	11110	12140	13600	14620
12	6860	7900	9090	10140	11330	12380	13870	14900
5	7250	8360	9620	10720	11980	13080	14660	15760
*Upto 5 Cyc with front loader	9240	10640	12250	13650	15260	16650	18660	20060
5 HT	6720	7750	8920	9940	11110	12140	13600	14620

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 03:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..