

AS 504 - Teknik Özellikler



Description

AS 504, temel olarak toprak işleme, uygulama ve malzeme elleçleme işlemleri için tasarlanmış, tarımsal sanayi amaçlı bir lastiktir. Mükemmel kendi kendini temizleme özellikleri ve daha iyi kavrama özelliklerine sahip olan bu lastik, tarla römorkları ve teleskopik yükleyiciler için uygundur. AS 504, belirli son kullanıcı gereksinimlerini karşılamak için çeşitli versiyonlarda sunulmaktadır: kesilme ve kopmaya karşı dirençli özel bir hamura sahip "HD" versiyonu ve daha uzun lastik ömrü sağlayan güçlendirilmiş gövdeye sahip "özel" versiyon.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Teleskopik yükleyici • Tarla römorku
Endüstriyel: Teleskopik yükleyici

Version	STANDARD
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	135 A8
LI/SS FREE ROLLING	148 A8

Dimensions International Standard

Ply Rating	16
Section Width (mm)	308
Overall Diameter (mm)	987
Static Loaded Radius (mm)	438
Rolling Circumference (mm)	2892
SRI (mm)	475
Rim Rec	W 9
Rim Alt	9 ; 11
ECE	E11-106R-004347

Load capacity (Kg)

km/h / bar	4.90
10 FR	4410
25 FR	3750
30 FR	3530
40 FR	3150
10 DW	3050
25 DW	2595
30 DW	2440
40 DW	2180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/17/2025 3:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..