

## AT 171 - Teknik Özellikler



### Description

AT 171 özellikle çamur bataklık traktörleri için tasarlanmıştır. Özel yönlü ve ekstra derin sırt tasarımı ıslak ve çamurlu yüzeylerde mükemmel çekiş sağlar.

### UM

International Standard

### Construction

BIAS

### Machinery

Zirai: ATV • Çamur bataklık traktörü

|           |                |
|-----------|----------------|
| Version   | STANDARD       |
| Type      | TL             |
| Tyre Size | AT 37 X 9 - 22 |
| LI/SS     | 88 A8/ 64 F    |

## Dimensions International Standard

|                            |      |
|----------------------------|------|
| Ply Rating                 | 8    |
| Section Width (mm)         | 205  |
| Overall Diameter (mm)      | 945  |
| Static Loaded Radius (mm)  | 444  |
| Rolling Circumference (mm) | 2778 |
| Rim Rec                    | W 7  |
| Rim Alt                    | W 6  |
| TRA Code                   | R1W+ |

## Load capacity (Kg)

|                     |      |      |
|---------------------|------|------|
| km/h / bar          | 1.40 | 1.00 |
| 40 MUD BOGGING      | 560  | -    |
| 80 MUD BOGGING      | 280  | -    |
| 40 CASUAL TRANSPORT | -    | 455  |
| 80 CASUAL TRANSPORT | -    | 230  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 22:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..