

AT 603 - Teknik Özellikler



Description

AT 603 är ett industridäck för lantbruk avsett för arbetsfordon och grävlaster. AT 603 har konstruerats för att säkerställa utmärkt hållbarhet och dragförmåga på drivhjulen och erbjuder maximal prestanda på alla underlag tillsammans med utmärkta självrensande egenskaper. AT 603 i "special"-version har förstärkt däckhölje, medan "HD"-versionen erbjuder förbättrad motståndskraft mot skärande underlag och punktering.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Bekoloder • Uygulamalı makine
Endüstriyel: Bekoloder

Version	SPECIAL
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	142 A8

Dimensions US Standard

Usa code	94033904
Ply Rating	12
Section Width (inch)	12.1
Overall Diameter (inch)	39.4
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	119.2
Rim Rec	W 9
Rim Alt	11
ECE	E4-106R-004350

Load capacity (lbs)

mph / psi	54
5 FR	8180
15 FR	6960
20 FR	6550
25 FR	5840
5 DW	5710
15 DW	4850
20 DW	4560
25 DW	4080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 02:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..