

AW 705 - Teknik Özellikler



Description

AW 705, toprak işleme ve taşıma uygulamalarında uygulamalı makine, römork ve balya makineleri için geliştirilmiştir. Geliştirilmiş dayanıklılık ve yüksek yük kapasitesi sayesinde modern tarım için idealdir.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Balya makinesi • Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	146 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	381
Overall Diameter (mm)	850
Static Loaded Radius (mm)	391
Rolling Circumference (mm)	2575
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E4-106R-001882

Load capacity (Kg)

km/h / bar	4.70
10 FR	4200
25 FR	3570
30 FR	3360
40 FR	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 22:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..