

AW 705 - Teknik Özellikler



Description

AW 705, toprak işleme ve taşıma uygulamalarında uygulamalı makine, römork ve balya makineleri için geliştirilmiştir. Geliştirilmiş dayanıklılık ve yüksek yük kapasitesi sayesinde modern tarım için idealdir.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Balya makinesi • Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20
LI/SS FREE ROLLING	151 A8

Dimensions US Standard

Usa code	94027408
Ply Rating	12
Section Width (inch)	16.3
Overall Diameter (inch)	42.7
Static Loaded Radius (inch)	19
Rolling Circumference (inch)	131.6
Rim Rec	13.0
Rim Alt	12 SDC ; 13 SDC ; 14
ECE	E4-106R-002711

Load capacity (lbs)

	mph / psi	44
	5 FR	10650
	15 FR	9050
	20 FR	8520
	25 FR	7610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 06:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..