

## BK 4040 - Teknik Özellikler



### Description

BK 4040, taşıma uygulamasında kullanılan tarım römorkları için özel olarak tasarlanmıştır. Güçlü gövde üstün yük kapasitesi ve dayanıklılık sağlar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Römork

Version	STANDARD
Type	TT
Tyre Size	7.00 - 16

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	198
Overall Diameter (mm)	770
Rim Rec	5.50
Rim Alt	5.00 F
ECE	E11-106R-005300

## Load capacity (Kg)

km/h / bar	4.70
30	1320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18/05/2025 04:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..