

BK 826 - Teknik Özellikler



Description

BK 826 lastiđi, nakliye uygulamaları alanındaki r morklar i in ustal kla tasarlanm şt r ve benzersiz dayanıklılık ve performans sunar. 'Harvester Special' versiyonu, hasat i in  zel olarak tasarlanm şt r ve tarlada optimum g venilirlik sađlar. Bu  apraz lastik, ađır hizmet g revlerinin taleplerini karřılamak i in olađan st  y k kapasitesi sunan g  lendirilmiř bir g vdeye sahiptir. Ek olarak, BK 826'nın  st n kesme ve talař direnci ile tasarlanm ř "End striyel" bir varyant  mevcuttur ve bu da onu zorlu kořullarda kazıcı y kleyiciler i in ideal bir se im haline getirir.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Bi erd ver • R mork

End striyel: Bekoloder • R mork

Version	HARVESTER SPECIAL
Type	TT
Tyre Size	9.00 - 16

Dimensions International Standard

Ply Rating	16
Section Width (mm)	265
Overall Diameter (mm)	925
Rim Rec	6.50 H
Rim Alt	6.00 G

Load capacity (Kg)

km/h / bar	7.25
30	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16/05/2025 22:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..