

COMMANDER TWIN RIB - Teknik Özellikler



Description

COMMANDER TWIN RIB, mükemmel kavrama sağlayan omuz çentikli, 4 kuşaklı desene sahip bir lastiktir. Geniş sırt profili iyi ağırlık dağılımı sağlar. Güçlü gövde, üstün sırt hamuru ile birlikte daha uzun lastik ömrü sağlar. COMMANDER TWIN RIB, toprak işleme ve taşıma uygulamaları için mükemmeldir.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Tek çeker traktör

Version	STANDARD
Type	TT
Tyre Size	5.00 - 15
LI/SS	82 A6

Dimensions International Standard

Ply Rating	6
TKPH	1
Section Width (mm)	145
Overall Diameter (mm)	665
Rim Rec	4.00 E
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.70
30	475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16.05.2025 22:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..