

CON STAR - Teknik Özellikler



Description

CON STAR özellikle tarımsal sanayi, kaldırma ve yükleme uygulamalarında kullanılan küçük yükleyiciler ve teleskopik yükleyiciler için uygundur. Müthiş dikey ve yatay sabitleme ile birlikte mükemmel çekiş özelliğine sahiptir. CON STAR, uzun lastik kullanım ömrüne katkıda bulunan kesilme ve kopmaya karşı dirençli bir hamurdan yapılmıştır.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Küçük yükleyici • Teleskopik yükleyici

Endüstriyel: Küçük yükleyici • Teleskopik yükleyici

Version	INDUSTRIAL
Type	TL
Tyre Size	380/75 - 20 (14.5 - 20)
LI/SS	148 A8

Dimensions US Standard

Usa code	94051519
Section Width (inch)	15.2
Overall Diameter (inch)	42.5
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	128.9
Rim Rec	W 12
Rim Alt	W 11 ; 12 SDC ; 12 ; W 13 ; 13 SDC ; 13
ECE	E11-106R-003022

Load capacity (lbs)

mph / psi	58
25	6940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16/05/2025 22:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..