

CON STAR - Teknik Özellikler



Description

CON STAR özellikle tarımsal sanayi, kaldırma ve yükleme uygulamalarında kullanılan küçük yükleyiciler ve teleskopik yükleyiciler için uygundur. Müthiş dikey ve yatay sabitleme ile birlikte mükemmel çekiş özelliğine sahiptir. CON STAR, uzun lastik kullanım ömrüne katkıda bulunan kesilme ve kopmaya karşı dirençli bir hamurdan yapılmıştır.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Küçük yükleyici • Teleskopik yükleyici

Endüstriyel: Küçük yükleyici • Teleskopik yükleyici

Version	INDUSTRIAL
Type	TL
Tyre Size	500/70 - 24 (19.5L - 24)
LI/SS	164 A8

Dimensions International Standard

Section Width (mm)	505
Overall Diameter (mm)	1300
Static Loaded Radius (mm)	579
Rolling Circumference (mm)	3926
SRI (mm)	625
Rim Rec	DW 16 L
Rim Alt	DW 15 L ; DW 18 L
ECE	E11-106R-003031

Load capacity (Kg)

km/h / bar	4.00
40	5000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/19/2025 5:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..