

EARTHMAX SR 42 - Teknik Özellikler



Description

EARTHMAX SR 42 madencilik veya ağır kütük uygulamalarında kullanılan yük vagonları için özel olarak tasarlanmış radyal yoldışı bir lastiktir. Ayırt edici sırt tasarımı üstün çekiş ve yanıl sabitlemenin yanı sıra buzlu ve karlı sert ve çakıllı arazilerde bile iyi frenleme ve viraj alma performansı sağlar. Gerçekten de kesilmeye ve aşınmaya dirençli özel sırt hamuru, ekstrem soğuk iklimler için özellikle uygundur. EARTHMAX SR 42 mükemmel dayanıklılık ve uzun bir hizmet ömrü için Tamçelik gövdeye sahiptir.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Yük vagonu

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 25
LI/SS	171 B

Dimensions US Standard

Usa code	94048984
TMPH	72
Overall Width (inch)	15
Overall Diameter (inch)	55.6
Static Loaded Radius (inch)	25.7
Rolling Circumference (inch)	166.6
Rim Rec	10.00/1.5
Rim Alt	--
Star Rating	***
TRA Code	E4
Tread Depth	48

Load capacity (lbs)

mph / psi	102	116
30	12800	13600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 01:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..