

## EARTHMAX SR 49 M - Teknik Özellikler



### Description

EARTHMAX SR 49 M, özellikle yeraltı madenciliğinde zorlu kayalık koşullarında çalışan dozerler, yükleyiciler, düşük profilli damperli kamyonlar (LPDT) ve yük taşıma damperleri (LHD) için tasarlanmış, özel yönsüz desene sahip Tamamen Çelik bir radyal lastiktir. EARTHMAX SR 49 M, olağanüstü çekiş ve sabitleme gerektiren zorlu işlemler için idealdir. L-4 derin sırt ve özel olarak formüle edilmiş UMS (yeraltı madeni hizmeti) hamuru, kaya kesiklerine ve delinmelere karşı mükemmel dirence ek olarak daha uzun bir lastik aşınma ömrü sağlar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Dozer • Yük taşıma damperli (LHD) • Yükleyici • Düşük profilli damperli kamyon

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Type      | TL                     |
| Tyre Size | 29.5 R 25              |
| LI/SS     | 208 A2                 |

## Dimensions US Standard

|                              |           |
|------------------------------|-----------|
| Usa code                     | 94058457  |
| Overall Width (inch)         | 30.7      |
| Overall Diameter (inch)      | 75        |
| Static Loaded Radius (inch)  | 33.2      |
| Rolling Circumference (inch) | 220.5     |
| Rim Rec                      | 25.00/3.5 |
| Star Rating                  | *         |
| TRA Code                     | L4        |
| Tread Depth                  | 72        |

## Load capacity (lbs)

|           |       |       |       |       |       |
|-----------|-------|-------|-------|-------|-------|
| mph / psi | 58    | 62    | 65    | 69    | 73    |
| 5         | 34200 | 35300 | 37500 | 38600 | 39700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 14:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..