

EARTHMAX SR 50 - Teknik Özellikler



Description

EARTHMAX SR 50 (L-5), yükleyiciler için özel olarak tasarlanmış, Tamamen Çelikten radyal bir lastiktir. Dayanıklı gövde ve yanak koruyucuları, en zorlu operasyonlar için idealdir. EARTHMAX SR 50, aşınma süresini uzatan, kesilmeye karşı dayanıklı özel bileşikten üretilmiştir. Araç kullanıcıları ayrıca kusursuz çekiş, istikrar ve konforlu sürüş özelliklerinden memnun kalırlar.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	216 A2

Dimensions US Standard

Usa code	94069637
Overall Width (inch)	30.5
Overall Diameter (inch)	74.8
Static Loaded Radius (inch)	33.9
Rolling Circumference (inch)	225.3
Rim Rec	25.00/3.5
Star Rating	**
TRA Code	L5
Tread Depth	121

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	41900	43000	44100	45400	46700	49400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18.05.2025 2:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..