

INDUSTRIAL RIB F3 - Teknik Özellikler



Description

INDUSTRIAL RIB F3 uygulamalı makineler ve römorklar ile arazi ve kara yolu taşımacılığı ve toprak işleme operasyonları için tasarlanmış, kuşaklı desene sahip bir tarımsal sanayi lastiğidir. Bu lastik, anızlara olağanüstü dayanıklı hamuruyla en kritik çalışma koşullarına uygundur ve uzun lastik kullanım ömrü sağlar.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	11L - 15 SL
LI/SS	117 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	279
Overall Diameter (mm)	813
Rim Rec	8 LB
Rim Alt	10 LB
ECE	E11-106R-004303
TRA Code	F3

Load capacity (Kg)

km/h / bar	4.20
30	1290
40	1160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 3:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..