

LIFT STAR PLUS - Teknik Özellikler



Description

LIFT STAR zorlu inşaat çalışmaları ve diğer ağır uygulamalarda kullanılan teleskopik taşıyıcılar için özel olarak tasarlanmış, çapraz kuşaklı bir lastiktir. Alçak profilli yanağı, yüksek kaldırma çalışmalarında kusursuz istikrar sağlarken, doğrusal olmayan diş tasarımı tırmanmada büyük ölçüde çok yönlülüğe imkan verir. Ek olarak, özel olarak tasarlanmış yanak, kesilme ve delinmeye karşı daha fazla koruma sağlar.

UM

US Standard

Construction

BIAS

Machinery

Endüstriyel: Teleskopik yükleyici

Version	STANDARD
Type	TL
Tyre Size	400/75 - 28

Dimensions US Standard

Usa code	94046225
Ply Rating	16
Section Width (inch)	15.7
Overall Diameter (inch)	51.9
Static Loaded Radius (inch)	23.3
Rolling Circumference (inch)	155.3
Rim Rec	12.00 GR
ECE	E11-106R-005330

Load capacity (lbs)

mph / psi	51	73
30	8545	-
5	-	13890

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 3:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..