

LUG STAR - Teknik Özellikler



Description

LUG STAR, olağanüstü çekiş gerektiren kara yolu-demiryolu ekskavatör uygulamaları için tasarlanmış endüstriyel bir lastiktir. Mükemmel kendi kendini temizleme özelliklerine ve çok dirençli bir sırt hamuruna sahiptir. Sağlam gövde mükemmel dayanıklılık sağlar.

UM

US Standard

Construction

BIAS

Machinery

Endüstriyel: Karayolu demiryolu ekipmanı

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

Dimensions US Standard

Usa code	94073580
Ply Rating	18
Overall Width (inch)	11
Overall Diameter (inch)	42.5
Static Loaded Radius (inch)	19.9
Rolling Circumference (inch)	131.6
Rim Rec	7.5
Rim Alt	7.0 ; 8.0

Load capacity (lbs)

mph / psi	145
5	15190
15	11685

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 04:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..