

MAGLIFT ECO RIB - Teknik Özellikler



Description

MAGLIFT ECO RIB, GSE (Ground Support Equipment, Zemin Destek Ekipmanı) römorkları için özel olarak tasarlanmış sağlam bir lastiktir. Güçlendirilmiş yapısı, kayma risklerini ortadan kaldırırken, özel olarak tasarlanmış jant koruması, tekerlek hasarına karşı koruma sağlar. MAGLIFT ECO RIB, römorklar için mükemmel direksiyon kontrolü, yüksek stabilite, düşük titreşim ve özerklik sunar. Bunlara ek olarak ayrıca düşük yuvarlanma direnci ve geliştirilmiş verimlilik için düşük ısı özellikleri mevcuttur.

UM

International Standard

Construction

◆ SOLID

Machinery

Endüstriyel: Forklift

Version

STANDARD

Type

Tyre Size

4.00 - 8

Dimensions International Standard

Section Width (mm)	104
Overall Diameter (mm)	406
Rim Rec	3.00 D - 8

Load capacity (Kg)

km/h / bar	-
5 OTHER VEHICLES	950
10 OTHER VEHICLES	860
25 OTHER VEHICLES	730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 04:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..