

MAGLIFT - Teknik Özellikler



Description

MAGLIFT, özellikle endüstriyel ve lojistik operasyonlarda forklift için tasarlanmıştır. Bu sağlam lastik, yüksek yük kapasitesi ve olağanüstü konfor sunar. MAGLIFT, uzun lastik ömrü sağlayan mükemmel kesilme ve kopma direnci sergiler. Takviyeli yapısı kayma risklerini ortadan kaldırırken, özel damak şekli jantta montaj işlemlerini basitleştirir.

UM

International Standard

Construction

◆ SOLID

Machinery

Endüstriyel: Forklift

Version

LIP - NON MARKING

Type

Tyre Size

27 X 10 - 12
(250/75 - 12)

Dimensions International Standard

Section Width (mm)	240
Overall Diameter (mm)	677
Rim Rec	8.00 G - 12

Load capacity (Kg)

km/h / bar	-
25 LOAD WHEEL	3900
25 STEER WHEEL	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 05:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..