

MULTI RIB - Teknik Özellikler



Description

MULTI RIB, tek çeker traktörler ve uygulamalı makineler ile toprak işleme ve taşıma uygulamalarına yönelik bir tarımsal sanayi lastiğidir. Uzun ömrü boyunca mükemmel kullanım sunar. Her ihtiyaç için çeşitli versiyonlar mevcuttur: delinme direnci geliştirilmiş bir "aramid kuşaklı" versiyon, kesilme ve kopmaya karşı dirençli özel bir hamurdan yapılmış "HD" versiyon.

UM

International Standard

Construction

❖ BIAS

Machinery

Zirai: Tek çeker traktör • Uygulamalı makine

Version	STANDARD
Type	TL
Tyre Size	11.00 - 16

Dimensions International Standard

Ply Rating	12
Section Width (mm)	315
Overall Diameter (mm)	930
Rim Rec	W10 L
Rim Alt	W 8 ; W 8 L
ECE	E11-106R-004649

Load capacity (Kg)

km/h / bar	4.10
40	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18.05.2025 04:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..